

according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Revision date: 02/25/2020

Supersedes: 02/25/2020

Supersedes: 02/25/2020 Form 1-389/20

SECTION: 1. Product and company identification

1.1. Product identifier

Product form : Substance

Name : Neon, Compressed

CAS No : 7440-01-9

Formula : Ne

Other means of identification: : Neon, Compressed

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Industrial use. Use as directed.

1.3. Details of the supplier of the safety data sheet

Concorde Specialty Gases, Inc. 36 Eaton Rd. Eatontown, NJ 07712 USA T (732) 5449899- F (732) 5449894

www.concordegas.com

1.4. Emergency telephone number

Emergency number CHEMTREC, 24hr/day 7days/week — Within USA: 1-800-424-9300, Outside USA: 001-703-527-3887

SECTION 2: Hazardsidentification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Compressed gas H280

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)



GHS04

Signal word (GHS-US) : WARNING

Hazard statements (GHS-US) : H280 - CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED

OSHA-H01 - MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION.

Precautionary statements (GHS-US) : P202 - Do not handle until all safety precautions have been read and understood

P271+P403 - Use and store only outdoors or in a well-ventilated place. CGA-PG05 - Use a back flow preventive device in the piping. CGA-PG10 – Use only with equipment rated for cylinder pressure

CGA-PG06 - Close valve after each use and when empty.

CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C (125°F).

2.3. Other hazards

Other hazards not contributing to the : Asphyxiant in high concentrations.

classification

Contact with liquid may cause cold burns/frostbite.

2.4. Unknown acute toxicity (GHS-US)

No data available

1/8

This document is only controlled while on the Concorde Specialty Gases, Inc. website and a copy of this controlled version is available for download.



according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Revision date: 02/25/2020

Supersedes: 02/25/2020

Form 1-389/20

SECTION 3: Composition/information on ingredients

3.1. Substance

Name	Product identifier	%
Neon, compressed (Main constituent)	(CAS No) 7440-01-9	100

3.2. Mixture

Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove vict

: Remove victim to uncontaminated area wearing self-contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

First-aid measures after skin contact : Adverse effects not expected from this product.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Hold the eyelids open and

away from the eyeballs to ensure that all surfaces are flushed thoroughly. Contact an

ophthalmologist immediately.

First-aid measures after ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

None.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire

5.2. Special hazards arising from the substance or mixture

Reactivity : No reactivity hazard other than the effects described in sub-sections below.

5.3. Advice for firefighters

Firefighting instructions

Evacuate all personnel from the danger area. Use self-contained breathing apparatus (SCBA) and protective clothing. Immediately cool containers with water from maximum distance. Stop flow of gas if safe to do so, while continuing cooling water spray. Remove ignition sources if safe to do so. Remove containers from area of fire if safe to do so. On-site fire brigades must comply with OSHA 29 CFR 1910.156 and applicable standards under 29 CFR 1910 Subpart L—Fire Protection.

Protection during firefighting

: Compressed gas: asphyxiant. Suffocation hazard by lack of oxygen.

Special protective equipment for fire fighters

: Use self-contained breathing apparatus. Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters.

Specific methods

Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas containers to rupture. Cool endangered containers with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.

Stop flow of product if safe to do so.

Use water spray or fog to knock down fire fumes if possible.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

: Try to stop release. Evacuate area. Ensure adequate air ventilation. Wear self-contained breathing apparatus when entering area unless atmosphere is proven to be safe. Stop leak if safe to do so.



according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Revision date: 02/25/2020

Supersedes: 02/25/2020

Form 1-389/20

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Try to stop release.

6.3. Methods and material for containment and cleaning up

No additional information available

6.4. Reference to other sections

See also sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Wear leather safety gloves and safety shoes when handling cylinders. Protect cylinders from physical damage; do not drag, roll, slide or drop. While moving cylinder, always keep in place removable valve cover. Never attempt to lift a cylinder by its cap; the cap is intended solely to protect the valve. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Never insert an object (e.g., wrench, screwdriver, pry bar) into cap openings; doing so may damage the valve and cause a leak. Use an adjustable strap wrench to remove over-tight or rusted caps. Slowly open the valve. If the valve is hard to open, discontinue use and contact your supplier. Close the container valve after each use; keep closed even when empty. Never apply flame or localized heat directly to any part of the container. High temperatures may damage the container and could cause the pressure relief device to fail prematurely, venting the container contents. For other precautions in using this product, see section 16.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Store in a cool, well-ventilated place. Store and use with adequate ventilation. Store only where temperature will not exceed 125°F (52°C). Firmly secure containers upright to keep them from falling or being knocked over. Install valve protection cap, if provided, firmly in place by hand. Store full and empty containers separately. Use a first-in, first-out inventory system to prevent storing full containers for long periods.

OTHER PRECAUTIONS FOR HANDLING, STORAGE, AND USE: When handling product under pressure, use piping and equipment adequately designed to withstand the pressures to be encountered. Never work on a pressurized system. Use a back flow preventive device in the piping. Gases can cause rapid suffocation because of oxygen deficiency; store and use with adequate ventilation. If a leak occurs, close the container valve and blow down the system in a safe and environmentally correct manner in compliance with all international, federal/national, state/provincial, and local laws; then repair the leak. Never place a container where it may become part of an electrical circuit.

7.3. Specific end use(s)

None.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Neon, compressed (7440-01-19)	
ACGIH	Not established
USA OSHA	Not established

8.2. Exposure controls

Appropriate engineering controls

: Oxygen detectors should be used when asphyxiating gases may be released. Consider work permit system e.g. for maintenance activities. Systems under pressure should be regularly checked for leakages. Provide adequate general and local exhaust ventilation.



according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Revision date: 02/25/2020

Supersedes: 02/25/2020

Form 1-389/20

Hand protection : Wear working gloves when handling gas containers.

Eye protection : Wear safety glasses with side shields or goggles when transfilling or breaking transfer

connections. Wear safety glasses with side shields.

Respiratory protection : Self-contained breathing apparatus (SCBA) or positive pressure airline with mask are to be

used in oxygen-deficient atmospheres.

Thermal hazard protection : None necessary.

Environmental exposure controls : None necessary

Other information : Wear safety shoes while handling containers.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Gas

Appearance : Colorless gas.

Molecular mass : 20 g/mol

Color : Colorless.

Odor : No odor warning properties.

Odor threshold : Odor threshold is subjective and inadequate to warn for overexposure.

Freezing point

Freezing point

-248.66°C

Boiling point

-246.1°C

Flash point

Not applicable.

Critical temperature

-228.7°C

Auto-ignition temperature

Decomposition temperature

Flammability (solid, gas)

No data available

Vapor pressure : Not applicable.

Critical pressure : 2760 kPa

Relative vapor density at 20 °C : No data available

Relative density : 1.204 at boiling point (water = 1)

Density : 1.086 g/cm³ liquid density at -400°F (-240°C); vapor density is 0.836

kg/cu meter @ 21.1°C, 1 atm

Specific gravity / density : 0.0061 g/cm³ (at 20°C)

Relative gas density : 0.7

Solubility : Water: 8.9 mg/l
Log Pow : Not applicable.
Log Kow : Not applicable.
Viscosity, kinematic : Not applicable.
Viscosity, dynamic : Not applicable.
Explosive properties : Not applicable.

Oxidizing properties : None.

Explosive limits : Non-flammable.

9.2 Other information

Gas group : Compressed gas

Additional information : None

4/8



according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Revision date: 02/25/2020

Supersedes: 02/25/2020

Form 1-389/20

5/8

SECTION 10: Stability and reactivity

10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

None.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified
Skin corrosion/irritation : Not classified

pH: Not applicable.

Serious eye damage/irritation : Not classified

pH: Not applicable.

Respiratory or skin sensitization : Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified Reproductive toxicity : Not classified Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated

exposure)

: Not classified

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : No ecological damage caused by this product.

12.2. Persistence and degradability

Neon, compressed (7440-01-9)	
Persistence and degradability	No ecological damage caused by this product

12.3. Bioaccumulative potential

Neon, compressed (7440-01-9)	
Log Pow	Not applicable.
Log Kow	Not applicable.
Bioaccumulative potential	No ecological damage caused by this product.



according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Revision date: 02/25/2020

Supersedes: 02/25/2020

Form 1-389/20

12.4. Mobility in soil

Neon, compressed (7440-01-9)	
Mobility in soil	No data available.
Ecology - soil	No ecological damage caused by this product.

12.5. Other adverse effects

Effect on ozone layer : None. Effect on the global warming : None.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations

Waste treatment methods : May be vented to atmosphere in a well ventilated place. Consult supplier for specific

recommendations. Do not discharge into any place where its accumulation could be

dangerous. Contact supplier if guidance is required.

Dispose of contents/container in accordance with local/regional/national/international regulations. Contact supplier for any special requirements.

: 2.2 - Class 2.2 - Non-flammable compressed gas 49 CFR 173.115

SECTION 14: Transportinformation

In accordance with DOT

Transport document description : UN 1065 Neon, compressed, 2.2

UN-No.(DOT) : UN1065

Proper Shipping Name (DOT) : Neon, compressed

Department of Transportation (DOT) Hazard

Classes

Hazard labels (DOT) : 2.2 - Non-flammable gas



Additional information

Emergency Response Guide (ERG) Number : 120 (UN1913); 121 (UN1065)

Other information : No supplementary information available.

Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's

compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting the containers: - Ensure there is adequate ventilation. - Ensure that containers are firmly secured. - Ensure cylinder valve is closed and not leaking. - Ensure valve outlet cap nut or plug (where provided)

is correctly fitted. - Ensure valve protection device (where provided) is correctly fitted.

Transport by sea

UN-No. (IMDG) : 1065

Proper Shipping Name (IMDG) : NEON, COMPRESSED

Class (IMDG) : 2 - Gases MFAG-No : 121

Air transport

UN-No.(IATA) : 1065

Proper Shipping Name (IATA) : Neon, compressed

Class (IATA) : 2

Civil Aeronautics Law : Gases under pressure/Gases nonflammable nontoxic under pressure



according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Revision date: 02/25/2020

Supersedes: 02/25/2020

Form 1-389/20

SECTION 15: Regulatory information

15.1. US Federal regulations

	Neon, compressed (7440-01-9)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
	SARA Section 311/312 Hazard Classes	Sudden release of pressure hazard

15.2. International regulations

CANADA

Neon, compressed (7440-01-9)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

Neon, compressed (7440-01-9)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

15.2.2. National regulations

Neon, compressed (7440-01-9)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. US State regulations

Neon, compressed (7440-01-9)	
U.S California - Proposition 65 - Carcinogens List	No
U.S California - Proposition 65 - Developmental Toxicity	No
U.S California - Proposition 65 - Reproductive Toxicity - Female	No
U.S California - Proposition 65 - Reproductive Toxicity - Male	No
State or local regulations	U.S Massachusetts - Right To Know List U.S New Jersey - Right to Know Hazardous Substance List U.S Pennsylvania - RTK (Right to Know) List



according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Revision date: 02/25/2020

Supersedes: 02/25/2020

Form 1-389/20

SECTION 16: Other information

Other information

: When you mix two or more chemicals, you can create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture. Consult an industrial hygienist or other trained person when you evaluate the end product. Before using any plastics, confirm their compatibility with this product.

Concorde asks users of this product to study this SDS and become aware of the product hazards and safety information. To promote safe use of this product, a user should (1) notify employees, agents, and contractors of the information in this SDS and of any other known product hazards and safety information, (2) furnish this information to each purchaser of the product, and (3) ask each purchaser to notify its employees and customers of the product hazards and safety information.

The opinions expressed herein are those of qualified experts within Concorde Specialty Gases, Inc. We believe that the information contained herein is current as of the date of this Safety Data Sheet. Since the use of this information and the conditions of use are not within the control of Concorde Specialty Gases, Inc., it is the user's obligation to determine the conditions of safe use of the product.

Concorde Specialty Gases, Inc. SDSs are furnished by Concorde or the independent distributors and suppliers who package and sell our products. To obtain current SDSs for

these products, contact your Concorde sales representative, local distributor, or supplier, or download from www.concordegas.com. If you have questions regarding Concorde's SDSs, would like the document number and date of the latest SDS, or would like the names of the

Concorde's suppliers in your area, phone or write Concorde Specialty Gases, Inc. Phone: (732)5449899; Address: 36 Eaton Rd. Eatontown, NJ 07712 USA

Full text of H-phrases:

Liquefied gas	Gases under pressure Liquefied gas
H280	CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED

NFPA health hazard : 0 - Exposure under fire conditions would offer no hazard


beyond that of ordinary combustible materials.

NFPA fire hazard : 0 - Materials that will not burn.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.

NFPA specific hazard : SA - This denotes gases which are simple asphyxiants.



HMIS III Rating

Health : 0 Minimal Hazard - No significant risk to health

Flammability : 0 Minimal Hazard
Physical : 3 Serious Hazard

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

8/8