

CONCORDE Tetrafluoromethane Safety Data Sheet

according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Revision date: 6/15/2022 Supersedes: 5/26/2019

Document 4-381/22 Last Revised 6/15/2022

SECTION: 1. Product and company identification

1.1. Product identifier

Product form : Substance

Name : Tetrafluoromethane

CAS No : 75-73-0 Formula : CF4

Other means of identification : Tetrafluoromethane (R14), Carbon tetrafluoride, F-14, refrigerant gas R14, perfluoromethane,

halon-14

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Industrial use. Use as directed.

1.3. Details of the supplier of the safety data sheet

Concorde Specialty Gases Inc.

36 Eaton Rd.

Eatontown, NJ 07724 USA www.concordegas.com

1.4. Emergency telephone number

Emergency number CHEMTREC: USA 1-800-424-9300, International 001-703-527-3887

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Compressed gas H280

Full text of H-phrases: see section 16

2.2. <u>Label elements</u>

GHS-US labeling

Hazard pictograms (GHS-US)



Signal word (GHS-US) : Warning

Hazard statements (GHS-US) : H280 - CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED

OSHA-H01 - MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION.

Precautionary statements (GHS-US) : P202 - Do not handle until all safety precautions have been read and understood

P271+P403 - Use and store only outdoors or in a well-ventilated place.

CGA-PG05 - Use a back flow preventive device in the piping.

CGA-PG10 - Use only with equipment rated for cylinder pressure.

CGA-PG06 - Close valve after each use and when empty.

CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C (125°F).

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

No data available



according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication. Revision date: 6/15/2022 Supersedes: 5/26/2019

Document 4-381/22 Last Revised 6/15/2022

SECTION 3: Composition/information on ingredients

3.1. Substance

Name : Tetrafluoromethane

CAS No : 75-73-0

Name	Product identifier	%
Tetrafluoromethane (R14)	(CAS No) 75-73-0	100

3.2. Mixture

Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep

victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

First-aid measures after skin contact : Adverse effects not expected from this product.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Hold the eyelids open and

away from the eyeballs to ensure that all surfaces are flushed thoroughly. Get immediate

medical attention.

First-aid measures after ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

None.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

5.2. Special hazards arising from the substance or mixture

Reactivity : No reactivity hazard other than the effects described in sub-sections below.

5.3. Advice for firefighters

Firefighting instructions : Evacuate all personnel from the danger area. Use self-contained breathing apparatus (SCBA)

and protective clothing. Immediately cool containers with water from maximum distance. Stop flow of gas if safe to do so, while continuing cooling water spray. Remove ignition sources if safe to do so. Remove containers from area of fire if safe to do so. On-site fire brigades must comply with OSHA 29 CFR 1910.156 and applicable standards under 29 CFR 1910 Subpart

L—Fire Protection.

Protection during firefighting : Compressed gas: asphyxiant. Suffocation hazard by lack of oxygen.

Special protective equipment for fire fighters : Use self-contained breathing apparatus. Standard protective clothing and equipment (Self

Contained Breathing Apparatus) for fire fighters.

Specific methods : Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat

radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems. Stop flow of product if safe to do so. Use water spray or fog to knock down

fire fumes if possible.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Prevent from o

: Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Try to stop release. Evacuate area. Ensure adequate air ventilation. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Stop leak if safe to do so.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available



according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Revision date: 6/15/2022 Supersedes: 5/26/2019

Document 4-381/22 Last Revised 6/15/2022

6.2. Environmental precautions

No additional information available

6.3. Methods and material for containment and cleaning up

No additional information available

6.4. Reference to other sections

See also sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Wear leather safety gloves and safety shoes when handling cylinders. Protect cylinders from physical damage; do not drag, roll, slide or drop. While moving cylinder, always keep in place removable valve cover. Never attempt to lift a cylinder by its cap; the cap is intended solely to protect the valve. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Never insert an object (e.g., wrench, screwdriver, pry bar) into cap openings; doing so may damage the valve and cause a leak. Use an adjustable strap wrench to remove over-tight or rusted caps. Slowly open the valve. If the valve is hard to open, discontinue use and contact your supplier. Close the container valve after each use; keep closed even when empty. Never apply flame or localized heat directly to any part of the container. High temperatures may damage the container and could cause the pressure relief device to fail prematurely, venting the container contents. For other precautions in using this product, see section 16.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Store in a cool, well-ventilated place. Store and use with adequate ventilation. Store only where temperature will not exceed 125°F (52°C). Firmly secure containers upright to keep them from falling or being knocked over. Install valve protection cap, if provided, firmly in place by hand. Store full and empty containers separately. Use a first-in, first-out inventory system to prevent storing full containers for long periods.

OTHER PRECAUTIONS FOR HANDLING, STORAGE, AND USE: When handling product under pressure, use piping and equipment adequately designed to withstand the pressures to be encountered. Never work on a pressurized system. Use a back flow preventive device in the piping. Gases can cause rapid suffocation because of oxygen deficiency; store and use with adequate ventilation. If a leak occurs, close the container valve and blow down the system in a safe and environmentally correct manner in compliance with all international, federal/national, state/provincial, and local laws; then repair the leak. Never place a container where it may become part of an electrical circuit.

7.3. Specific end use(s)

None.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Tetrafluoromethane (75-73-0)		
ACGIH	Not established	
USA OSHA Not established		
Tetrafluoromethane (R14) (7	5-73-0)	
Tetrafluoromethane (R14) (7: ACGIH	5-73-0) Not established	

8.2. Exposure controls

Appropriate engineering controls

: Ensure exposure is below occupational exposure limits (where available). Oxygen detectors should be used when asphyxiating gases may be released. Systems under pressure should be regularly checked for leakages. Provide adequate general and local exhaust ventilation. Consider work permit system e.g. for maintenance activities.

Hand protection

: Wear working gloves when handling gas containers.

Eye protection

: Wear safety glasses with side shields. Wear goggles and a face shield when transfilling or breaking transfer connections.



according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Revision date: 6/15/2022 Supersedes: 5/26/2019

: When workplace conditions warrant respirator use, follow a respiratory protection program that Respiratory protection meets OSHA 29 CFR 1910.134, ANSI Z88.2, or MSHA 30 CFR 72.710 (where applicable). Use

an air-supplied or air-purifying cartridge if the action level is exceeded. Ensure that the respirator has the appropriate protection factor for the exposure level. If cartridge type respirators are used, the cartridge must be appropriate for the chemical exposure (e.g., an organic vapor cartridge). For emergencies or instances with unknown exposure levels, use a

self-contained breathing apparatus (SCBA).

Thermal hazard protection Wear cold insulating gloves when transfilling or breaking transfer connections. None necessary.

Environmental exposure controls Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for

specific methods for waste gas treatment.

Other information : Wear safety shoes while handling containers.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties 9.1.

Physical state : Gas

Appearance : Colorless gas. Molecular mass 88 g/mol Colorless. Color

Odor : No data available

Odor threshold Odor threshold is subjective and inadequate to warn for overexposure.

3740 kPa

pΗ : Not applicable. Relative evaporation rate (butyl acetate=1) : No data available Relative evaporation rate (ether=1) : Not applicable. Melting point : -184 °C Freezing point : -183.59 °C

Boiling point : -128.06 °C Flash point : Not applicable. Critical temperature -45.7 °C Auto-ignition temperature : Not applicable. Decomposition temperature : No data available Flammability (solid, gas) : No data available Vapor pressure : Not applicable.

Critical pressure Relative vapor density at 20 °C : No data available Relative density : Not applicable.

Liquid density: 81.28 lb/ft3 (1.302 g/cm3) at -112°F (-80°C); Gas density 0.228 lb/ft3 (3.65 Specific gravity / density

kg/m3) at 70°F (21.1°C), 1 atm

Relative gas density : 3

Solubility : Water: 20 mg/l

Log Pow 1.18

Log Kow Not applicable. Viscosity, kinematic : Not applicable. Viscosity, dynamic : Not applicable. Explosive properties : Not applicable.

Oxidizing properties : None.

Non flammable. **Explosive limits**

Other information 9.2.

Gas group : Liquefied gas

Additional information Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground

Document 4-381/22

Last Revised 6/15/2022



according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication. Revision date: 6/15/2022 Supersedes: 5/26/2019

Document 4-381/22 Last Revised 6/15/2022

SECTION 10: Stability and reactivity

10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.

10.2. **Chemical stability**

Stable under normal conditions.

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. **Incompatible materials**

Aluminum. Carbon dioxide >1832°F (1000°C). Alloys with >2% magnesium in the presence of water.

10.6. **Hazardous decomposition products**

If involved in a fire the following toxic and/or corrosive fumes may be produced by thermal decomposition: Fluorine. Carbonyl fluoride.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified Skin corrosion/irritation : Not classified pH: Not applicable.

: Not classified

Serious eye damage/irritation

pH: Not applicable.

Respiratory or skin sensitization : Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified : Not classified Reproductive toxicity Specific target organ toxicity (single exposure) : Not classified Specific target organ toxicity (repeated : Not classified

exposure)

No known effects from this product.

: Not classified Aspiration hazard Not applicable.

SECTION 12: Ecological information

12.1. **Toxicity**

Ecology - general : No data available. No ecological damage caused by this product.

12.2. Persistence and degradability

Tetrafluoromethane (75-73-0)		
Persistence and degradability	No ecological damage caused by this product.	
Tetrafluoromethane (R14) (75-73-0)		
Persistence and degradability	No data available.	

12.3. **Bioaccumulative potential**

Tetrafluoromethane (75-73-0)		
Log Pow	1.18	
Log Kow Not applicable.		
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.	
Tetrafluoromethane (R14) (75-73-0)		
Log Pow	1.18	
Bioaccumulative potential Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section		



according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Revision date: 6/15/2022 Supersedes: 5/26/2019

Document 4-381/22 Last Revised 6/15/2022

12.4. Mobility in soil

Tetrafluoromethane (75-73-0)		
Mobility in soil	No data available.	
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.	
Tetrafluoromethane (R14) (75-73-0) Ecology - soil Because of its high volatility, the product is unlikely to cause ground or water pollution.		

12.5. Other adverse effects

Effect on ozone layer : None. Global warming potential [CO2=1] : 5700

Effect on the global warming : Contains fluorinated greenhouse gases covered by the Kyoto protocol.

Calculated GWP of mixture: 5700 For quantities refer to cylinder label.

Effect on the global warming : Contains Fluorinated greenhouse gases covered by the Kyoto protocol.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Do not attempt to dispose of residual or unused quantities. Return container to supplier.

SECTION 14: Transport information

In accordance with DOT

Transport document description : UN1982 Tetrafluoromethane, 2.2

UN-No.(DOT) : UN1982

Proper Shipping Name (DOT) : Tetrafluoromethane

Department of Transportation (DOT) Hazard

Classes

Hazard labels (DOT) : 2.2 - Non-flammable gas



Additional information

Emergency Response Guide (ERG) Number : 126

Other information : No supplementary information available.

Special transport precautions

: Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers:

- Ensure there is adequate ventilation. - Ensure that containers are firmly secured. - Ensure cylinder valve is closed and not leaking. - Ensure valve outlet cap nut or plug (where provided)

is correctly fitted. - Ensure valve protection device (where provided) is correctly fitted.

: 2.2 - Class 2.2 - Non-flammable compressed gas 49 CFR 173.115

Transport by sea

UN-No. (IMDG) : 1982

Proper Shipping Name (IMDG) : TETRAFLUOROMETHANE (REFRIGERANT GAS R 14)

Class (IMDG) : 2 - Gases MFAG-No : 126

Air transport

UN-No.(IATA) : 1982

Proper Shipping Name (IATA) : REFRIGERANT GAS R 14

Class (IATA) : 2

Civil Aeronautics Law : Gases under pressure/Gases nonflammable nontoxic under pressure



according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Revision date: 6/15/2022 Supersedes: 5/26/2019

Document 4-381/22 Last Revised 6/15/2022

SECTION 15: Regulatory information

15.1. US Federal regulations

Tetrafluoromethane (75-73-0)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Sudden release of pressure hazard	

All components of this product are listed on the Toxic Substances Control Act (TSCA) inventory

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

Tetrafluoromethane (75-73-0)		
Listed on the Canadian DSL (Domestic Substances List)		
WHMIS Classification Class A - Compressed Gas		
Tetrafluoromethane (R14) (75-73-0)		
Listed on the Canadian DSL (Domestic Substances List)		
WHMIS Classification Class A - Compressed Gas		

EU-Regulations

Tetrafluoromethane (75-73-0)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Liquefied gas H280

Full text of H-phrases: see section 16

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Not classified

15.2.2. National regulations

Tetrafluoromethane (75-73-0)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

15.3. US State regulations

Tetrafluoromethane(75-73-0)	
U.S California - Proposition 65 - Carcinogens List	No
U.S California - Proposition 65 - Developmental Toxicity	No
U.S California - Proposition 65 - Reproductive Toxicity - Female	No
U.S California - Proposition 65 - Reproductive Toxicity - Male	No
State or local regulations	U.S New Jersey - Right to Know Hazardous Substance List

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

Tetrafluoromethane (R14) (75-73-0)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)



according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication. Revision date: 6/15/2022 Supersedes: 5/26/2019

Document 4-381/22 Last Revised 6/15/2022

Tetrafluoromethane (R14) (75-73-0)				
No	No	No	No	
Tetrafluoromethane (R14) (75-73-0)				
U.S New Jersey - Right to Know Hazardous Substance List				

SECTION 16: Other information

Revision date

Other information

When you mix two or more chemicals, you can create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture. Consult an industrial hygienist or other trained person when you evaluate the end product. Before using any plastics, confirm their compatibility with this product.

Concorde Specialty Gases, Inc. asks users of this product to study this SDS and become aware of the product hazards and safety information. To promote safe use of this product, a user should (1) notify employees, agents, and contractors of the information in this SDS and of any other known product hazards and safety information, (2) furnish this information to each purchaser of the product, and (3) ask each purchaser to notify its employees and customers of the product hazards and safety information.

The opinions expressed herein are those of qualified experts within Concorde Specialty Gases, Inc. We believe that the information contained herein is current as of the date of this Safety Data Sheet. Since the use of this information and the conditions of use are not within the control of Concorde Specialty Gases, Inc., it is the user's obligation to determine the conditions of safe use of the product.

Concorde SDSs are furnished on sale or delivery by Concorde or the independent distributors and suppliers who package and sell our products. To obtain current SDSs for these products, contact your Concorde Specialty Gases, Inc. sales representative, local distributor, or supplier, or download from www.concordegas.com. If you have questions regarding Concorde's SDSs, would like the document number and date of the latest SDS, or would like the names of the Concorde's suppliers in your area, phone or write the Concorde's Call Center (Phone: (732)544-9899; Address: Concorde Specialty Gases, Inc. 36 Eaton Rd. Eatontown NJ, 07712 USA

Concorde's and the Flowing Airstream design are trademarks or registered trademarks of Concorde Specialty Gases, Inc. in the United States and/or other countries.

Full text of H-phrases:

Compressed gas	Gases under pressure Compressed gas
Liquefied gas	Gases under pressure Liquefied gas
H280	CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED


NFPA health hazard : 1 - Exposure could cause irritation but only minor residual

injury even if no treatment is given.

NFPA fire hazard : 0 - Materials that will not burn.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.



HMIS III Rating

Health : 0 Minimal Hazard - No significant risk to health

0 Minimal Hazard Flammability : 3 Serious Hazard Physical